

PANEL IS TO BE INSTALLED PER SPECIFICATIONS AND ATLAS ROOFING'S INSTALLATION INSTRUCTIONS DWG. # 38127-10910

NOTE: ALL FASTENERS BY OTHERS (SEE INSTALLATION INSTRUCTIONS FOR RECOMMENDATIONS)
COVER SHIPPED LOOSE

"H" DIMENSION:

- 6" Coverage
- 8" Coverage
- 10" Coverage
- 12" Coverage*
- 14" Coverage*
- 16" Coverage*
- Other*: _____

COVER:

- 24 Ga. (.65 mm) Galv. Steel*
- .040" (1.01 mm) Aluminum*
- .063" (1.60 mm) Aluminum
- 22 Ga. (.81 mm) Galv. Steel
- .050" (1.27 mm) Aluminum
- Other _____

* Coverages over 10" include 1/8" stiffening band (see dwg # 38527-10879 for a reference)

Color: _____ Finish: _____

QUANTITIES:

_____ Lineal Feet (12'-0" (3.65 M) Lengths)

_____ Peak Miters

SEE ADDITIONAL PRINT APPROVAL FOR RAKE CONDITION


Fabrication will proceed only after receipt of signed print approval.

Print Approval:

Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance with Atlas Roofing's printed instructions.

Approved by: _____

Date: _____

PROJECT:		Phone: 855-542-0918	
ARCHITECT:		Fax: 800-770-3934 roof.atlasroofing.com	
CONTRACTOR:	DATE: 3/10/11	SHT.# ___ OF ___	
REPRESENTATIVE:	DRN BY: MRK	DWG# 38027-10909	
	CKD BY: SAK		