




Atlas Nail Base Fastener^{TP}

Thread Point Nailable Insulation Fastener

DESCRIPTION: Thread Point Nailable Insulation Fastener with Gimlet Thread Point. Specially engineered fastener for attaching Atlas ACFoam[®] Nail Base and ACFoam[®] CrossVent[®] to wood and timber substrates. Atlas Nail Base Fasteners are required for proper mechanical attachment of all ACFoam[®] Nailable Insulation Systems.



- MATERIAL:** Case hardened and Tempered Carbon Steel
- HEAD STYLE/DRIVE:** Pancake Head with T-30 Internal Drive
- HEAD DIAMETER:** 0.625"
- SHANK DIAMETER:** 0.190"
- THREAD LENGTH:** 2.750"
- OVERALL LENGTH:** 2" thru 18"
- POINT:** Gimlet Thread
- COATING:** Epoxy E-Coat (black)
- Passes more than 15 cycles (Kesternich) in accordance with DIN 50018*



PRODUCT SELECTION

IN	MM	PKG. QTY.
2.0	51	500/PAIL
2.5	64	500/PAIL
3.0	76	500/PAIL
3.5	89	500/PAIL
4.0	102	500/PAIL
4.5	114	500/PAIL
5.0	127	500/PAIL
5.5	140	500/PAIL
6.0	152	500/PAIL
6.5	165	500/PAIL
7.0	178	500/PAIL
7.5	191	500/PAIL
8.0	203	500/PAIL
8.5	216	250/PAIL
9.0	229	250/PAIL
10.0	254	250/PAIL
11.0	279	250/PAIL
12.0	305	250/PAIL
13.0	330	250/BOX
14.0	356	250/BOX
15.0	381	250/BOX
16.0	406	250/BOX
18.0	457	250/BOX

TENSILE STRENGTH	SHEAR STRENGTH	HEAD PULL-THRU VALUE ¹ (7/16" OSB)
3,380 lbf	2,900 lbf	545 lbf

WITHDRAWAL VALUES IN WOOD ¹							
Specific Gravity	0.67	0.55	0.50	0.46	0.43	0.36	0.31
lb/in.	1429	1173	1067	981	917	768	661

¹"Head Pull-Thru" and "Withdrawal" data reflect average ultimate values.

T-30 DRIVER BIT



NOTE: Two T-30 Driver Bits included in each package.

Note: All tests were conducted by an independent testing laboratory. Test results are offered only as a guide and are not guaranteed in any way by Atlas Roofing Corporation.

Other than the aforementioned representations and descriptions, Atlas Roofing Corporation (hereafter, "Seller") makes no other representations or warranties as to the insulation sold herein. The Seller disclaims all other warranties, express or implied, including the warranty of merchantability and the warranty of fitness for a particular purpose. Seller does, however, have a limited warranty as to the LTRR-Value of the insulation, the terms of which are available upon request from the Seller. Seller shall not be liable for any incidental or consequential damages including but not limited to the cost of installation, removal, repair or replacement of this product. Buyer's remedies shall be limited exclusively to, at Seller's option, the repayment of the purchase price or resupply of product manufactured by Atlas in a quantity equal to that of the nonconforming product. Atlas distributors, agents, salespersons or other independent representatives have no authority to waive or alter the above limitation of liability and remedies.