REFERENCE DETAIL:	

TECHNI-FLO RV SLOPE TO SLOPE, SHINGLED VERSION

EOD HIGH SNOW LOAD CONDITIONS

				TONTIGITSNC	DW LOAD CONDITIONS
					U.S. PATENT # 8,075,376 B1
ENDCAPS 8" (203 mm) WIDE — CONCEALED SPLICE PLATE AT EACH JOINT					ACTUAL LINEAL FOOTAGE OF RIDGE
INTERMITTENT SPACE 8" (203 mm) O.0			DGEVENT COVER 2-0" (3.65 m) LENG	THS)	ACTUAL LINEAL FOOTAGE OF EAVE
CONTINUOUS 20 GA. (1.01 mm) GALV. Z BRACKET				.050 (1.27 m	FASTENERS OTHERS m) EXPANDED PORT SCREEN
STYLE B					40
RIDGE OPENING EXISTING SHINGLED ROOF DIMENSION DETERMINED BY ATLAS ROOFING					
FASCIA IS TO BE INSTALLED PER SPECIFICATIONS AND ATLAS ROOFING'S INSTALLATION INSTRUCTIONS DWG. # 38124-14981					
Fabrication will proceed only after receipt of signed print approval.					PITCH
Print Approval: Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance with Atlas Roofing's printed instructions.	CrossVent:		=	(.65 mm) Galv. Steel (1.27 mm) Aluminum	.040" (1.01 mm) Aluminum .063" (1.60 mm) Aluminum
Approved by:			Other		
Date:			Color:		Finish:
PROJECT:		QUANTITIES:			Phone: 855-542-0918 Fax: 800-770-3934
ARCHITECT:		Lineal Feet (12'-0" (3	3.65 m) Lengths)	ATLAS	roof.atlasroofing.com
CONTRACTOR:		End Cap (12" (305 m	nm) Lengths)	DATE: 02/06/12	SHT.# OF
REPRESENTATIVE:		Style A	Style B	DRN BY: JJC CKD BY: SAK	DWG# 38024-14983 A