REFERENCE DETAIL:	TECHNI-FLO RV SLOPED ROOF MEETS FLAT ROOF			
		SLOI LD NO	OF MEETS LEAT NOOF	
SPECIFICATION REQUIREMENT FOR SQ. IN. OF NET FREE AIR PER LINEAL FT. (IF APPLICABLE) WATER DAM FASTENER (BY OTHERS) FASTEN FASTEN FASTEN FASTEN BY OTHER DIMENSION CALCULATED BY ATLAS	ER SUPF	SPLICE PLATE 12 GA. GALV. RACKET	ROOF PITCH	
SHINGLED ROOF SHOWN IF STANDING SEAM CONDTION, PLEASE SUPPLY HEIGHT OF STANDING SEAM ACTUAL LINEAL			PLYWOOD	
FOOTAGE OF RIDGE	COVER:			
ACTUAL LINEAL FOOTAGE OF EAVE	.050" (1.27	5 mm) Galv. Steel	.040" (1.01 mm) Aluminum .063" (1.60 mm) Aluminum	
RIDGE VENT IS TO BE INSTALLED PER SPECIFICATIONS AND ATLAS	Color:	Finis	sh:	
ROOFING'S INSTALLATION INSTRUCTIONS DWG #38124-10924	CrossVent:			
Fabrication will proceed only after receipt of signed print approval.		Air Spac	ce	
Print Approval: Architect and/or contractor shall verify all dimensions, sizes	QUANTITIES:			
the contract of the contract o		l Feet (12'-0" (3.65 M) Lengths)		
Approved by:	Right En		nd Cap (12" (305 mm) Lengths)	
Date:	Left End Cap (12" (305 mm) Lengths)			
PROJECT:			Phone: 855-542-0918	
ARCHITECT:		ATLAS	Fax: 800-770-3934 roof.atlasroofing.com	
CONTRACTOR:		DATE: 3/10/11	SHT.# OF	
REPRESENTATIVE:		DRN BY: MRK CKD BY: SAK	DWG# 38024-10923 C	