
EnergyShield[®] CGF Pro Continuous Wall Insulation







Introducing a new coated glass faced insulation for commercial exterior walls.

- Easy to incorporate into commercial wall design
- High R-value for a higher performance building envelope
- Multiple NFPA fire tested assemblies

Why EnergyShield[®] CGF Pro

Efficient: Our high performance Class A rated polyiso is extremely energy efficient, with the highest R-value per inch of any rigid insulation.

Durable: Added durability helps to protect the integrity of the continuous insulation layer by resisting jobsite damage, particularly in masonry and metal panel assemblies.

Permeable: Coated glass facers (CGF) are permeable and engineered to allow vapor movement versus foil facers that create vapor barriers.

Proven: EnergyShield[®] CGF Pro coated glass facer technology is proven with over 25 years of use as a facer in commercial walls.

Compatible: Engineered for compatibility with adhesives used in many of today's high performance exterior commercial wall assemblies.

Versatile: Offers design choices of non reflective facers.

Provides the durability needed in masonry, brick veneer and metal applications.



RODUCT CERTIFIED FOR LOW HEMICAL EMISSIONS: UL.COM/GG

The configuration of weather resistive barriers and/or air barriers used in conjunction with EnergyShield[®] CGF Pro is the responsibility of the designer. Atlas recommends sealing into rough opening flashing and to other portions of the building, including the roof and below grade. Atlas EnergyShield[®] CGF Pro facers are compatible with most standard joint fillers, sealants and adhesives. Consult the product manufacturer for specific compatibility.

2000 RiverEdge Parkway, Suite 800, Atlanta, Georgia 30328

wall.atlasroofing.com



201709_AtlasWall_CGFproSalesSheet_GGG

CONNECTING FUNCTION WITH FACILITY[™]