

DESCRIPTION

Atlas EnergyShield® Pro is a high performance thermal insulation board composed of a closed cell polyisocyanurate foam core with a reflective aluminum foil facer on one side and a white acrylic-coated aluminum foil facer on the other.

APPLICATIONS

Provides continuous insulation for Type I-V construction.

- Exterior framed walls with wood or steel studs
- Exterior walls of masonry or concrete
- Exterior framed walls with or without sheathing
- Interior exposed walls or ceilings
- Attics and crawlspaces without requiring a thermal barrier
- Air and water resistive barrier when installed accordingly

PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	VALUES
COMPRESSIVE STRENGTH	ASTM D1621	25 psi
FLAME SPREAD	ASTM E84 / UL 723	≤25
SMOKE DEVELOPMENT	ASTM E84 / UL 723	≤450
WATER VAPOR TRANSMISSION, METHOD A	ASTM E96	≤0.1 Perm at 1-inch
WATER ABSORPTION	ASTM C209/ASTM C1763	<1% by Volume
FLEXURAL STRENGTH	ASTM C203	40 psi, min @
DIMENSIONAL STABILITY, LENGTH & WIDTH	ASTM D2126	≤1% Linear Change
SERVICE TEMPERATURES	-	-100°F to +250°F
MOLD RESISTANCE	UL 2824	4, Highly Resistant
AIR PERMEANCE	ASTM E2178	<0.02L/s·m ² @ 75 Pa

Technical and physical properties listed are representative of typical values based on testing and are intended as general guidelines only and subject to manufacturing tolerances. No warranties are given except for those specifically written by Atlas for its products.

SUSTAINABILITY

Atlas polyiso insulation is manufactured using environmentally responsible processes and formulations.

- Contains no CFCs, HCFCs or HFCs
- Zero Ozone Depletion Potential (ODP)
- Negligible Global Warming Potential (GWP)
- GREENGUARD Gold Certification
- Contributes to LEED credits

For more information visit

wall.atlasrwi.com/about-wall/sustainability

ADVANTAGES

EnergyShield Pro provides multi-functional protection by addressing the necessary control layers to create a high performing wall assembly and provides installation efficiency.



THERMAL



WATER



AIR



VAPOR

CODE COMPLIANCE

- **ASTM C1289 Type I, Class 1 and 2**
- **ASHRAE 90.1**
- **ASHRAE 189.1**
- **International Energy Conservation Code (IECC), Section 402**
- **International Green Construction Code (IgCC)**
- **International Building Code (IBC), Section 2603**
- **International Residential Code (IRC), Section R316**
- **California Thermal Insulation Directory, T 1231**
- **ASTM E2178** Air Barrier Material
- **ASTM E2357** Air Barrier Assembly
- **ASTM E331** Water Penetration
- **ICC-ES AC71** Water-Resistive Barrier
- **DrJ TER 2202-01** Weather Resistive Properties
- **ICC-ES ESR-1375**
- **ICC-ES AC12, Appendix A**
- **DrJ TER 1306-03** Fire Performance
- **ASTM E84 / UL 723, Class A**
- **NFPA 285** Compliant within numerous wall assemblies
- **ANSI/UL 263 / ASTM E119:** 1, 2, 3 or 4 hour Fire Rated Assemblies as listed in the UL Product iQ™
- **NFPA 286** Interior exposed walls or ceilings only

PRODUCT DATA

NOMINAL THICKNESS	R-VALUE *	RSI	RECYCLED CONTENT	PIECES PER PACKAGE	SQ. FT. PER PACKAGE
0.5"	3.3	0.58	9.2%	86	2,752
0.75"	5.0	0.88	10.5%	58	1,856
1.0"	6.5	1.14	11.2%	45	1,440
1.5"	9.8	1.73	12.1%	30	960
1.6"	10.5	1.85	12.3%	27	864
2.0"	13.1	2.31	12.6%	22	704
2.5"	16.0	2.82	13.0%	18	576
3.0"	19.7	3.47	13.2%	15	480
3.1"	20.2	3.56	13.2%	15	480
3.5"	22.2	3.91	13.4%	13	416
4.0"	26.0	4.58	13.5%	11	352

*Thermal values were determined by ASTM C518 Test Method at 75°F mean temperature using materials conditioned in accordance with ASTM C1289.
 *R means resistance to heat flow. The higher the R-value, the greater the insulating power.
 Additional sizes available upon request. EnergyShield Pro is shipped on standard 48' truck with 24 packages per load. Truckload quantities may vary when mixed.

**FOR A COMPLETE LIST
OF PRODUCT SIZES,
SCAN TO DOWNLOAD THE
PACKAGE & LOADING GUIDE**



PRECAUTIONS

- Polyiso may contribute to flames and smoke spread when exposed to an ignition source of sufficient heat and intensity.
- Refer to local building codes for proper selection and placement of weather resistant barriers in a wall assembly for optimal air, moisture, and vapor control.
- EnergyShield Pro is not a structural product; follow local building code requirements.
- While EnergyShield Pro is approved for interior exposed applications, always refer to local building codes.

HANDLING

- While EnergyShield Pro is a water resistant product, products shall be kept dry while being stored horizontally. Reference EnergyShield Pro placard for storage and handling instructions.
- EnergyShield Pro should be covered with exterior cladding within 180 days of installation.

WARRANTY

EnergyShield Pro is backed by a Limited 15-Year Thermal Warranty.
 For complete terms and conditions, visit wall.atlasrwi.com/warranty



Atlas Roofing Corporation
 2000 Riveredge Parkway, Suite 800 • Atlanta, GA • 30328
 770-952-1442 • wall.atlasrwi.com

