



Small Space, Big Impact

EnergyShield XR transforms crawlspaces into high-performance zones improving energy efficiency, preventing moisture damage, and supporting long-term home value.



FOR CRAWLSPACE APPLICATIONS



Max R-value, Minimal Thickness. Achieve R-10 with just 1.5" of insulation. EnergyShield® XR delivers an impressive R-6.5 per inch, helping reduce material volume on the jobsite.



Easy to Install. Lightweight and easy to handle, EnergyShield XR can be easily cut and snapped. Ideal for tight or low-clearance crawl spaces.



Moisture Resistant. The closed-cell structure and non-absorbing facers resist water absorption, helping maintain consistent performance across all climates.



Proven Mold Resistance. Rated highest for mold resistance per UL 2824 for added confidence in humid, enclosed environments.



Insulation + Vapor Barrier. Combines thermal efficiency with vapor control when seams are properly sealed.



Health-Conscious & Certified. GREENGUARD Gold certified for low chemical emissions – no harmful off-gassing, now or over time.



Versatile Application. Versatile performance for every part of the building envelope. Install EnergyShield XR below grade, under slab, in crawl spaces, and on exterior walls. Simplify your project with one trusted solution.

No Ignition Barrier Required.

Refer to [*Did You Know: Attics & Crawlspaces*](#) for additional information.

